

# FAL 5645 Automatic L-Sealer

## Robust and Value Priced

Selected by Sealed Air  
Technology Engineered by Shanklin®  
CT Approved Shrink Packaging Machinery



Sealed Air Shrink Packaging creates value for our customers by delivering technologically differentiated and sustainable solutions.

**Sealed Air Sustainability**

**Meeting Sustainable Packaging Needs Without Compromising Performance or Value!**

# SeleCTech™ FAL 5645

## Automatic L-Sealer

- Fully automatic wrapper
- Easy Load film unwind
- Machined hot knife sealing system
- Delivers strong thin package seals
- CE approved model available
- Right-to-left product flow
- Easy access electrical control panel
- Brush backed pin perforator
- Adjustable height film inverting head and take away conveyor

### Quality Comes Standard

The SeleCTech™ Model FAL 5645 is the economically priced, robustly built automatic wrapping machine. The machine features gentle product feed and straight line product feed that makes it ideally suited for handling a wide variety of products. The FAL 5645 features conveyor fed automatic operation and is capable of up to 30 packs per minute. The L-seal design provides great flexibility and quick product change. The machine will accept randomly spaced product, fed either automatically or manually.

### SeleCTech™ Model FAL 5645 Specifications

<b>Sealer Size (mm) L x W</b> <b>Sealer Size (inches) L x W</b>	565 x 460 22 x 17.7
<b>Package Size (mm) L x W x H</b> <b>Package Size (inches) L x W x H</b>	(100 ~ 450) x (60 ~ 350) x (5 ~ 120) (4 ~ 17.7) x (2.4 ~ 13.7) x (.2 ~ 4.7)
<b>Floor Space (mm) L x W x H</b> <b>Floor Space (inches) L x W x H</b>	1795 x 985 x 1570 70.8 x 39 x 22.5
<b>Package Speeds</b>	Up to 30 packs per minute
<b>Power Requirements (by model):</b> <b>SLCT-FAL5645 (CE)</b> <b>SLCT-FAL5645</b>	1 Phase, 230 V, 14 A, 3.5 KW, 50 HZ (with neutral) 1 Phase, 240 V, 14 A, 3.5 KW, 60 HZ (no neutral)
<b>Pneumatic Requirements</b>	55 PSI, 4 Kg / sq cm
<b>Mechanical Adjustments</b>	<ul style="list-style-type: none"><li>• Film roll guides</li><li>• Perforator positions</li><li>• Film inverting head</li><li>• Product infeed table</li></ul>
<b>Electrical Controls</b>	<ul style="list-style-type: none"><li>• Horizontal and vertical photo eyes for accurate bag seal placement</li><li>• Seal bar temperature controls</li><li>• Dwell time controls for quality sealing</li></ul>
<b>Other Standard Features</b>	<ul style="list-style-type: none"><li>• Integrated selvage winder</li><li>• Caster included</li><li>• Floor stabilizers included</li><li>• Emergency stops and machine reset</li></ul>
<b>Optional Features</b>	<ul style="list-style-type: none"><li>• Closing conveyor for short product transfer</li></ul>

**Engineered for use with all Sealed Air Shrink Packaging Films  
Including Cryovac® Technology (CT) Micro-Layered Shrink Films**